



## Sustainable Cord

<b>Country of Origin</b>	Designed and Manufactured in Australia	
<b>Launch</b>	1987 by Living Fabrics, now Sustainable Living Fabrics	
<b>Application</b>	Woven upholstery fabric suitable for domestic, commercial and public seating, fixed and movable acoustic panels or screens.	
<b>End Use Classification</b> AS 2687-1997 : Table 2	Classification 5 Commercial Heavy Duty. Performance complies to all End Use Classifications 1 - 5	
<b>Environmental LCA</b> ISO 14024	Audited by Bureau Veritas Australia and New Zealand and licensed to carry Australia's ISO 14024 Type 1 Ecolabel, GECA Textiles & Leather TLv3.0-2014	
<b>Carbon Neutral</b>	Certified Carbon Neutral by Climate Active.	
<b>Building Programs</b>	Architects Declare product Aware WELL NABERS & LEED Infrastructure Sustainability Council of Australia's IS rating program Green Building Council of Australia's GREEN STAR rating program	
<b>Low emitting TVOC's</b> ASTM D5116-97	Total Volatile Organic Compound Specific area Emission rate :	<0.005 mg/m2/hr
<b>Composition</b> <b>HS Code</b>	97% Australian Ecowool with No FR or PFAS chemicals Woven Fabric of Combed Wool, Dyed	5112.19
<b>Width / Roll</b>	137cm / 30m approx.	
<b>Mass</b>	approx. 460g/m2 approx. 644gms/linear metre	
<b>Repeat and Colours</b>	No Repeat, 20 woven colourways Colour variations may occur from batch to batch, check before cutting.	
<b>Special Colours</b>	Special colours available on request, subject to minimum order quantity.	
<b>Abrasion Resistance</b> AS 2001.2.25-2006	Martindale Method : Meets Abrasion Resistance requirements of AS2687 for Classification 5 Commercial Heavy Duty.	72,000

<b>Early Fire Hazard Test</b> AS/NZS 1530.3-1999, ISO 5660	Ignitability Index: (Range 0 - 20) Spread of Flame Index: (Range 0 - 10) Heat Developed Index: (Range 0 - 10) Smoke Developed Index: (Range 0 - 10)	15 0 0 4
<b>Regulatory Indices</b>		
<b>IMO Resolution</b> A.652 (16) 8.2 & 8.3 (BS 5852 : ISO 5660)	Did Ignition Occur Assembly smouldering when dismantled: Test assembly self extinguished Flame Time	No No Yes NA Minutes
<b>Cone Calorimeter Fire Test</b> AS/NZS 3837:1998	Average Heat Release Rate : Average Specific Extinction Area : (to be less than 250m <sup>2</sup> /kg in unsprinklered buildings) Product Group Number Classification :	43.4 kW/m <sup>2</sup> 40.4 m <sup>2</sup> /kg  Group 2
<b>Pilling</b> TWC TM 196-2009	Mean Rating : (where best is 5, CTA = 3-4) Classification 5 Commercial Heavy Duty.	4
<b>Yarn Slippage : Standard Seam</b> AS 2687-1997	Warp: 180 N Weft 180 N Upholsterer to use an upholstery seam designed for extra strength	6.5mm 5.0mm
<b>Care and Cleaning</b>	With regular care and cleaning this fabric will maintain it's appearance for many years. Vacuum regularly, protect from exposure to direct sunlight. Gently wipe clean with a damp cloth or consult a professional dry cleaner.	
<b>Warranty</b>	12 years. See terms and conditions on <a href="http://sustainablelivingfabrics.com.au">sustainablelivingfabrics.com.au</a>	
<b>Environmental</b>	Licensed to carry GECA's Textiles and Leather (TLv3.0-2014) Ecolabel, and Certified Carbon Neutral by Climate Active. Pesticide use is strictly limited and known aquatic toxins prohibited. No illegal harvest of wood and fibre for raw materials. Biodegradable substances must be used in manufacturing. Waste management and energy use strategies in place. Limits on heavy metals in final product. Restrictions or bans on known carcinogens, mutagens or other specific toxic substances including potentially cancer causing dyes and dye by-products. No unsubstantiated claims(greenwashing). Workers can expect fair pay, equal opportunity and safe working environment. Manufacturers must comply with International Labour Organisation Conventions for no forced labour or worker exploitation.	
<b>Benefits of Wool</b>	Durable Biodegradable Anti Static Naturally Flame Resistant Renewable Comfortable	